

Features

- High reliability
- For large current
- Low power consumption
- Extended measuring range
- For railway

Open Loop Type




Specifications

Ta=25°C

Product name	Code:2215		CA3-500
	Symbol	Unit	
Nominal input current	If(n)	AT	±500
Saturation current	If(s)	AT	±550
Nominal Output Voltage	Vh	V	±10±0.100 [at If(n)]
Load resistance	RL	Ω	2k
Offset Voltage	Vo	V	0±0.030 [at 0A]
Supply Voltage	Vcc	V DC	±15±5%
Consumption Current	Icc	mA	±35 Max.
Response Speed	Trr	μ sec	15 Max. [at di/dt=100A/μ sec]
Thermal Drift of Vh		%/°C	±0.05 Max. [at Ta=-40 to+80°C]
Thermal Drift of Vo		mV/°C	±0.8 Max. [at Ta=-40 to+80°C]
Dielectric Strength		kV	AC 2.5 [with 50 or 60 Hz 1min.]
Insulation Resistance		Ω	500M Min. [at 500V DC]
Operating Temperature	Ta	°C	-40 to +80
Storage Temperature	Ts	°C	-40 to +85
Hysteresis Error		mV	35 Max. [at If --> 0]

Dimensions

Unit : mm




Connector Type[SMS 4PH-4JD28] Maker[SOURIAU]

CA3-21027

Product Name	Mass
CA3-500	228g

Connection



NANA ENGINEERING NANA ENGINEERING CO.,LTD.

Machida 310 Irago building 4F
 1-22-5 Morino, Machida-shi, Tokyo 194-0022
 E-Mail : nanaeng_sales@nana-e.com
 URL : <http://www.nana-e.com>